

NR Premium 20%



Auto & Architectural

Non-Reflective Premium 20% window tinting provides enhanced privacy by blocking visibility from the outside while maintaining a sleek, dark appearance. It reduces glare and UV rays, protecting interiors from fading and heat buildup. The non-reflective nature ensures a consistent look without dark reflections, offering both style and function for cars, homes, or offices. This film is signal friendly and made for internal use.

Technical Performance Data

Calculated on 3mm single-pane glass.

Natural Light & Glare

VLT (Visible Light Transmission)	20%
Visible Light Reflectance (internal)	12%
Glare Reduction	72%

Solar Energy

Transmittance	32%
Reflectance	17%
Absorption	51%
Total Solar Energy Rejected (TSER)	55%

Thermal Energy

Shading Coefficient	0.56
Solar Heat Gain Coefficient	0.50
U-Value - (W/m ² K)	5.8
R-Value - (m ² K/W)	0.17

Ultraviolet & Infrared

UV Rejection	99%
IR Rejection	11%
Anti Fade Rating (0-100)	72

Manufactured Specifications

Thickness	50 µm
Structure	2 Ply
Composition	PET
Warranty	7 Years
Colour	Natural
Stock Code	NRP20

For Reference Only: Technical specifications can differ between batches. Dura Vista retains the right to update this information at any time without notice.

Product Care & Maintenance:

After installation allow 30 – 60 days to cure. Never try to remove bubbles during the curing process. After curing you may clean the windows with soapy water and non-abrasive cloths or sponges and paper towels. Do not attempt to clean the film with chemicals containing ammonia or abrasives.

Installation Guidelines

Vertical Installation on standard glass surface

Single Pane Glass

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	!
Thermally Toughened Safety Glass (EN 12150)	✓

Double Pane / Double Glazing

Clear Double Pane	✓
Tinted Double Pane	!
Reflective Tinted Double Pane	X
Gas-Filled Double Pane (Low-E)	X
External: SATDIP / PVB / Lam. Safety Glass	✓
Internal: SATDIP / PVB / Lam. Safety Glass	!
Thermally Toughened Safety Glass (EN 12150)	✓

Safety Guideline Symbols

	Symbol
Safe to install	✓
Unsafe to install	X
Caution, will cause thermal stress	!

Safety Performance

For Internal use only	✓
Peel Strength (gr/inch)	>1800
Signal Interference	0%
REACH & RoHS Respected	✓
Flammability Test Pass ISO 3795	✓

Guidelines provided are based on a single glass surface up to 2.5 m² with no single length or width greater than 2 meters.

