



White Out

White-Out film is ideal for total privacy and a clean, modern look. Perfect for offices, conference rooms, or glass partitions, it completely blocks visibility while allowing light to diffuse softly. Durable and easy to install, it protects against UV rays and enhances aesthetics, making it a practical solution for privacy and design needs. This film is warranted for **10 years** if it has no direct sunlight contact, and **5 years** with direct sunlight contact. This film is made for internal use.

Technical Performance Data

Calculated on 3mm glass

Natural Light & Glare

VLT (Visible Light Transmission)	1%
Visible Light Reflectance (internal)	73%
Glare Reduction	89%

Solar Energy

Transmittance	24%
Reflectance	60%
Absorption	16%
Total Solar Energy Rejected (TSER)	-

Thermal Energy

Shading Coefficient	0.33
Solar Heat Gain Coefficient	-
U-Value - (W/m ² K)	-
R-Value - (m ² K/W)	-

Ultraviolet & Infrared

UV Rejection	99%
IR Rejection	98%
Anti Fade Rating (0-100)	99

Manufactured Specifications

Thickness	60 µm
Structure	1 Ply
Composition	PET
Warranty	5/10 Years
Colour	White
Stock Code	WHITE

For Reference Only: Technical specifications can differ between batches, Dura Vista retains the right to update this information at any time without notice.

Product Care & Maintenance:

After installation allow 30 – 60 days to cure. Never try to remove bubbles during the curing process. After curing you may clean the windows with soapy water and non-abrasive cloths or sponges and paper towels. Do not attempt to clean the film with chemicals containing ammonia or abrasives.

Installation Guidelines

Vertical Installation on standard glass surface

Single Pane Glass

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Thermally Toughened Safety Glass (EN 12150)	✓

Double Pane / Double Glazing

Clear Double Pane	!
Tinted Double Pane	X
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane (Low-E)	X
External: SATDIP / PVB / Lam. Safety Glass	X
Internal: SATDIP / PVB / Lam. Safety Glass	X
Thermally Toughened Safety Glass (EN 12150)	✓

Safety Guideline Symbols

Safety Guideline Symbols	Symbol
Safe to install	✓
Unsafe to install	X
Caution, will cause thermal stress	!

Safety Performance

For Internal use only	✓
Peel Strength (gr/inch)	>1800
REACH & RoHS Respected	✓
Flamability Test Pass ISO 3795	✓

Guidelines provided are based on a single glass surface up to 2.5 m² with no single length or width greater than 2 meters.

